

Floor Care

Description

A natural breathable milky polish for surfaces coated with The Natural Paint Company varnishes, waxes and oils and other similar coatings. Biodegradable and fast drying, The Natural Paint Company Floor Care forms a silky, anti-slip satin finish which enhances and protects the surface from both dirt and mechanical wear. Regular use will prolong the life of the surface coating. Floor Care contains no chemical preservatives, chlorides, ammonia or phosphates.

Uses

To refresh and maintain oiled, waxed and varnished interiors including:

- Timber surfaces
- Linoleum
- Cork
- Terracotta tiles
- Concrete

Container Sizes

- 1 Litre, 2 Litre, 5 Litre

Ingredients

Water, carnauba wax, microwax, fatty acid alcohol-ester, lavender oil, bergamot oil (contains limonene).

Applying the Product

1. Use only when varnish, oil or wax is well hardened – wait at least 4 weeks after final coating.
2. Clean area first. Use a gentle, non-abrasive pH neutral cleaner. We recommend The Natural Paint Company Household Cleaner.
3. Spot clean again where necessary.
4. Apply Floor Care thinly and evenly with a lint free cloth or floor mop/sponge. Use at a rate of 100-150mls to 5 litres of lukewarm water.
5. Frequency of application depends on the substrate and wear.

Note: The Natural Paint Company Floor Care might change the sheen level, surface appearance and characteristics of some finishes. Apply to a test piece or area first to establish suitability of the treated surface.



Safety Precautions

Natural ingredients can still be harmful to users and the environment if misused, or if accidents occur, so please carefully observe the following:

- Keep out of reach of children.

Storage

- Seal well and keep in a cool dry place. Protect from frost.

Disposal

- Do not dispose of large quantities in drains and wastepipes.
- Recycle empty containers where possible. Dispose of according to council regulations.

Disclaimer

The above information is given as a general guide only. Site conditions will vary, and it is always advisable to apply a test sample. Failure to follow the above instructions will void all warranties attached to the product. This supersedes any previous data sheets.

